

Work saver.

**Designed.
Engineered.
Remarkable
Value.**



WORKSAVER®

SNOW BLADES

Snow Blades for Skid Steers and Tractor Front Loaders.



- **Blade floats to clean uneven surfaces.**
- **Reinforced 21" or 27" high 10-gauge moldboards provide long service life.**
- **3/8" x 6" cutting edge of 1044 steel.**
- **Blade locks for grading loose dirt or gravel.**

- **Ideal for residential or commercial snow removal. Use on driveways, parking lots, or other large areas.**
- **7.5-ft. & 9-ft. models feature 5° lateral oscillation to allow blade to follow ground contours.**
- **Two trip springs for controlled break over in snow.**



- **Step-through design allows for easy access to skid steer seat.**
- **Quick hook on skid steers or front loaders equipped with "Universal" mounting plate.**
- **Blade angles right or left.**
- **Adjustable skid shoes are 1/2" thick and rotate for long life.**

Worksaver

**Designed.
Engineered.
Remarkable
Value**

Worksaver Snow Blade Specifications

Model	SBFL-27108A	SBS-27108A	SBFL-2790A	SBS-2790A	SBFL-2172	SBS-2172	SBFL-2160	SBS-2160
Overall Width (in/cm)	108 / 274	108 / 274	90 / 229	90 / 229	72 / 183	72 / 183	60 / 152	60 / 152
Overall Height (in/cm)	27 / 69	27 / 69	27 / 69	27 / 69	21 / 53	21 / 53	21 / 53	21 / 53
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
Cutting Edge (in/mm) 3/8 x 6 / 9.525 x 152.4	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
5° Lateral Oscillation	Standard	Standard	Standard	Standard	NA	NA	NA	NA
Extension Trip Springs	2	2	2	2	2	2	2	2
Man. Angle Positions	NA	NA	5	5	5	5	5	5
Width @ Full Angle	96 / 244	96 / 244	80 / 203	80 / 203	62 / 157	62 / 157	52 / 132	52 / 132
Tractor Loader Mount	*Brkts. Req.	NA	*Brkts. Req.	NA	*Brkts. Req.	NA	*Brkts. Req.	NA
Skid Steer Mount	NA	Universal	NA	Universal	NA	Universal	NA	Universal
Adjustable Skid Shoes	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Horse Power Range	40-95 HP	40-95 HP	30-80 HP	30-80 HP	<40 HP	<40 HP	<40 HP	<40 HP
Weight (lb/kg)	665 / 302	690 / 313	555 / 252	530 / 240	366 / 166	350 / 159	347 / 157	334 / 152
Front Loader Hydraulic Angle Kit	Standard	NA	Optional	NA	Optional	NA	Optional	NA
SS Hyd. Angle Kit	NA	Standard	NA	Optional	NA	Optional	NA	Optional
Crossover Rel. Valve	Standard	Standard	Optional	Optional	Optional	Optional	Optional	Optional
Optional Top Deflector	360230	360230	360227	360227	360223	360223	360220	360220
Opt. Sight Indicator	360235	360235	360235	360235	360235	360235	360235	360235
Snow Blade Item No.	360075	360070	360040	360000	360160	360130	360140	360100

*Optional Interfacing Quick Attach brackets available for most popular loaders.
Note: *Be sure tractor / skid steer is properly counterbalanced.*

Worksaver, Inc.

P.O. Box 100, Litchfield, IL 62056-0100
Phone: 217-324-5973 * Fax 217-324-3356
E-mail sales@worksaver.com
Web. www.worksaver.com

Information Provided By:



Worksaver Inc. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Worksaver Inc. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.



**READ AND UNDERSTAND OPERATOR'S
MANUAL BEFORE OPERATION.**



**NEVER ALLOW CHILDREN OR
BYSTANDERS AROUND SNOW BLADE
WHEN YOU ARE USING EQUIPMENT.**