

# CIMARRON

by **WOODS**

## WOODSBATWING

BW180 Series 3  
flex wing rotary cutter

**NEW!**  
AND IMPROVED.



**WOODS**  
The Attachment Experts.™

**6**  
YEAR  
GEARBOX  
WARRANTY



**CIMARRON**by **WOODS****BW180 SERIES 3 BATWING®**

## BW180 15-Foot Batwing

Woods took rotary cutters to a new level of performance when we introduced the first Batwing in 1964—leading the industry in innovation and performance ever since. Over the years, Woods engineers continually improved the line, adding such features as quick-change blade systems. **Innovative design** features like the **smooth, sloped deck, extra-deep side frames, and fully baffled decks** make Woods Batwings more productive and more durable than imitators.

The BW180 15' Batwing flex wing cutter incorporates many exclusive design features found in our heavy-duty BW1800. Designed to provide the performance of a medium-duty cutter at an affordable price, the BW180's smooth, sloped top deck sheds water and debris, resisting rust and corrosion—while carrying a 10-year rust-through warranty. A 13-inch deep side frame offers maximum material capacity. The CV drive is available on our 540 and 1000 rpm models, while the equal angle drive is available only for 540 rpm models. The BW180 features a 160 hp divider gearbox and three 120 hp spindle gearboxes that perform powerfully and reliably for years and years—our six-year warranty ensures it. Designed for low-cost and easy maintenance, the BW180 is your best buy for durable, reliable performance.

The BW180 Batwing cutter also comes available in a one-wing (two sections—center and one wing) 10.5' model, the BW126.

So go on, compare us to other folding wing rotary cutters. You'll discover why a Woods Batwing is the original—and still the best.

### STANDARD-DUTY BW180

#### 45-160 PTO hp tractors

- Cat 6 CV drive has higher torque capacity than competitors' Cat 5
- Smooth, sloped deck sheds water and debris, resisting rust and corrosion, 10-year deck rust-through warranty
- 160/120 hp gearboxes with 6-year limited warranties ensure years of worry-free performance
- CV driveline available on 540 rpm and 1000 rpm models (equal angle drive available only for 540 rpm models)
- Deep, 13-inch side frame for maximum material capacity
- Innovative wing design allows close trimming to objects
- Full-length, replaceable side skids feature a large wear surface for greater durability and a formed angle to prevent scalping
- Standard stump jumpers protect gearbox from obstructions and six inches of blade overlap ensure a clean cut
- Full-length, 1-inch hinge pin outlasts shorter hinges found on competition
- Floating cylinder link on each wing extends cylinder life
- Safety lock easily secures deck for safe, simple transporting
- Quick change blade pins – an industry exclusive
- Spring axle protection on all models
- Shielding options – rubber belting (standard), single or double row chain shielding (optional)
- Wheel options – laminated solid tires, used aircraft tires, foam-filled aircraft tires, or 15" wheel rims (without tires) and optional dual wheels for both center and wing sections



## Gearbox and Deck Warranties

All gearboxes carry 6-year limited warranties while deck carries a 10-year rust-through warranty to ensure years of worry-free performance.



## Greaseable pivot points

All pivot points on the turnbuckle and axle arms are lubricated to increase durability and reduce wear. The wheel yoke is straddle mounted and pinned in seven places to further improve durability and service life.

## Fully baffled deck

Baffling system allows for finer shred and better distribution of cut material while greatly reducing windrowing.



## Easy access

Flip-up shields offer full and easy access to the drive, clutches, and gearbox.



## PERFORMANCE GUIDE

Ideal for maintaining grassy fields, pastures, and waterways, and cutting weeds and light brush up to two inches in diameter.

## Deep, 13-inch side frame

13-inch side frame and sloped deck has greater material capacity for efficient, productive cutting.

\* Shown with optional single row chain shielding. Also available with optional double row chain shielding. Rubber shielding standard.

## Safety shield options

Rubber belting comes standard. Single, or double row chain shielding is optional.

## Narrow transport width

Wings independently fold up to 96-inch transport width and lock securely for quick and easy transport.

## Specifications

Model	BW180-3
Cutting width	180"
Overall width	190"
Transport width	96"
Overall length	180"
Weight	3,920 lbs.
Cutting height	1"-15"
Cut capacity	2" diameter
Deck thickness	10 ga.
Side skirt thickness	1/4"
Side skirt depth	13"
Wing flex	90° up/ 22° down
Hinge rod diameter	1"
Equal Angle Input Drive	Cat 5 Heavy
CV Input Drive	Cat 6
Wing Drive	Cat 4
Drivetrain configuration	4 gearbox
<b>Gearbox hp rating</b>	
Power divider	160 hp
Center and wings	120 hp
<b>Gearbox warranty</b>	6-years
Output shaft diameter	2"
No. of spindles	3
Blade pin diameter	1-1/2"
Blades	1/2" x 4"
Blade carrier	Round
Blade overlap	6"
<b>Tip speed</b>	
540 rpm	14,965 fpm
1000 rpm	15,450 fpm
<b>Tractor hp</b>	45-160 hp

**CIMARRON**

by **WOODS**

Batwing® is a registered trademark of Woods Equipment Company.